



Tightening handle for phase clamps

Code: P249

The tightening handle is an accessory that can be used in special conditions for the application of short-circuiting clamps when, given the small space, workers cannot use insulating sticks appropriate to the installation voltage ($U_{n\max} = 20 \text{ kV}$), situations specified in the internal work safety regulations of the users and to avoid their application by hand.

The tightening handle is provided with a "RO bayonet" socket coupling system which can be adjusted in two positions : fixed or folded.

The handle is not (and does not replace) an insulating stick because it does not provide the protection distance between the operator and the power installation but it allows the installation of clamps on conductors without any hand contact.

The use of the tightening handle in activities that do not meet the conditions specified by the safety regulations in force exonerate the manufacturer from any responsibility.
The handle is approximately 440 mm long.



Adapters and accessories with "RO bayonet" coupling rod

SR EN 61230



Adapters and accessories with "RO bayonet" coupling rod are elements that can be assembled temporarily in "RO bayonet" foldable coupling systems of insulating sticks consisting of PMU and PMP models to allow attachment to the stick of various protective equipment (short-circuiting device clamps, voltage detectors, anchoring elements for work at height). Adapters and accessories can be made of plastic or metal and are manufactured in the following constructive versions:

- AF E-C adapter - provided with coupling system with "hexagon 12" socket
- AR E-C adapter - provided with coupling system with "hexagon 12" socket with 30°, 60°, 90° folding
- AF E-U adapter - provided with universal coupling system
- AF E-DIN adapter - provided with coupling system with "DIN bayonet" socket
- AB/DTTU-Tv - for the coupling of the urban transport detector type DTTU-Tv



AF E-C



AR E-C



AF E-U



AF E-DIN



AF E-K



AB/DTTU-Tv

Device for the handling of MV fuses

Code: P2459

The device for the remote handling of MV fuses (diameters between 35 - 90 mm) is a device that can be installed temporarily in the coupling system with "RO bayonet" socket of multipurpose connectable insulating sticks (PMU or PMP type).

The device jaws close / open by the rotation of the stick.

