



### Detachable anchoring and fixing device, provided with cord for KRAUSE ladders

SR EN 795



Code: P 2398

The detachable anchoring and fixing device, provided with fall arrester system, used on KRAUSE extensible / multipurpose ladders, is intended for anchoring and fixing this type of ladders on poles of various cross-sections (on circular poles with diameters between 150 ÷ 600 mm and on poles with rectangular cross-section with sides of maximum 450 x 335 mm), to prevent their tilting or slip, as well as the protection against falling of a worker climbing up/down or working on the ladder at height, by means of a sliding fall arrester on a flexible anchoring support.

This anchoring device for Krause ladders has the following distinctive characteristics:

- It is completely removable from the ladder and can be mounted / dismantled from the ladder without any auxiliary tools and without tampering with the ladder in any way.
- The ladder guiding system on the pole includes a system of V-shaped rollers mounted on the metallic chassis of the device.
- The chassis of the anchoring device is mounted on the ends of the rails of the top section and includes a locking device on the last rung of the ladder which prevents the accidental detachment of the device.
- The flexible anchoring system is tensioned with a tensioning and locking system consisting of a strap of adjustable length, a carabiner and a locking device.

The anchoring and fixing system with fall arrester used on KRAUSE aluminium ladders consists of the following elements:

- Detachable anchoring metallic chassis provided with support rollers on the pole** - 1 piece
- Flexible anchoring device provided with sliding fall arrester and energy absorber** - 1 piece
- Tensioning and locking system of the flexible anchoring support** - 1 piece
- Guiding adapter for the flexible anchoring support** by means of the telescopic insulating stick extended to 9 metres, in order to arrange it on the central rod of the device, in order to fasten the ladder on the pole or to dismantle it - 1 piece

#### WARNING!

The detachable anchoring and fastening system provided with flexible anchoring support, fall arrester, used on KRAUSE ladders, can only be used by a single person.

The detachable anchoring and fixing device with cord, together with the flexible anchoring support, the tensioning and locking system and the guiding adapter is delivered in a waterproof protective bag.



#### Technical characteristics

|  |       |
|--|-------|
| Static strength (daN/3 minutes)            | 1.200 |
| Dynamic strength (kg/3 m)                  | 100   |
| Maximum operating load (daN)               | 120   |
| Weight (kg) (without fall arrester system) | 2,5   |

